

LE- series

Industrial bench- and floor scale for general weighing in dry environments.

Rechargeable battery, stainless steel platform and several capacities and platform sizes.





- ✓ Platform in stainless steel.
- ✓ Indicator bracket for wall or table mount.
- ✓ Re-chargeable battery included.
- ✓ Communication RS-232C.
- ✓ 25 mm wide angle LCD-display with backlight.
- ✓ NET / GROSS function.
- ✓ TARE function.
- ✓ Unit conversion.



LE- series, specifications

| Technical standards | LE2-30 | LE2-60 | LE2-150 |
|---------------------------|-----------------------------------|-------------------|-------------------|
| Capacity | 30 kg | 60 kg | 150 kg |
| Readout | 10 g | 20 g | 50 g |
| Accuracy | +/- 10 g | +/- 20 g | +/- 50 g |
| Platform size | 325 x 320 x 52 mm | | |
| Stainless steel platform | | ✓ | |
| Weight of scale | | 3,8 kg | |
| | | | |
| | LE3-150 | LE4-300 | LE5-300 |
| Capacity | 150 kg | 300 kg | 300 kg |
| Readout | 50 g | 100 g | 100 g |
| Accuracy | +/- 50 g | +/- 100 g | +/- 100 g |
| Platform size | 450 x 350 x 60 mm | 600 x 600 x 60 mm | 950 x 500 x 70 mm |
| Weight of scale | 6,3 kg | 11 kg | 15,5 kg |
| ' | | | |
| Common standards | | | |
| Display | 25 mm LCD-display with backlight | | |
| Wall bracket included | ✓ | | |
| OIML-approved | × | | |
| Weighing technology | 4 x strain gauge loadcells | | |
| External adjustment | ✓ | | |
| Communication | RS232C | | |
| | | | |
| Functions | | | |
| Auto off function | √ | | |
| Units | Kg, Lb | | |
| Tare | ✓ | | |
| Battery function | Rechargeable battery: 7,2V 0,8 Ah | | |
| Mains adaptor | | ✓ | |
| | | | |
| Approvals & verifications | | | |
| CE-approval | ✓ | | |
| EC type approved | | * | |
| | | | |