

Floor scale for Medical use

User Manual

MBPA-250



www.liden-weighing.se


2020-09-01

SPECIFICATION


Modell	MBPA-250
Max kapacity	250 kg
Readabillity	100 g (0,1 Kg)
Accuracy	OIML Klass III
Tara	100 %
Min. loading	2 kg

Specification	
Display	25 mm heigh, 5 segment, LCD-display with background light
Construction	Steel pipe construction
Product size	440x340 mm
Platforme size	440x340x1050 mm
Stabilization time,	3 Second standard
approx	
Operating temerature	0°C - 40°C / 32°F - 104°F
Power supply	7,5V/1A AC adapter and 6xAA Battery
EU-verified in accordance with 2014/31 / EU	Klass III
MDD approved in accordance with 93/42/EEC	Klass I

Keypad



Keypad funtion



Symbols

→0←	Zero mode on
NĖT	Net display / Scale is tared in position
♦	Recalled value
HOLD	Lock (hold) mode
0	Stable mode on
	Operation & Key functions
0	On/Off Press briefly to switch the scale on and off.
() >0+	-

The tare button is used to tare things that are weighed together with the patient (eg clothes, shoes or other). Do this: place a weight (clothes, shoes or other) on the scale. Press $\Rightarrow T \in$ to remove this weight. The display will show NET.

Remove (clothes, shoes or other) and press $[+\tau]$ to exit tare function.

Manual or automatic hold function

In zero mode, you can use the manual or automatic hold function by pressing HOLD the display shows **Hold Auto** eller **Hold Off**.

Manual hold: Stand on the scale. Wait for the stable value, then press to lock the value.

The display returns to zero after about one second. The value is retrieved by pressing local Cancel.

Automatic Hold: Set Hold Auto as above by pressing Stand on the scale. At stable weight, the scale will automatically lock the value. If the weight after locking changes more than 4 kg, the scale is activated again and, when the scale is stable, will again automatically lock the value.

BMI

BMI – Body Mass Index


- 1. Put a person on the scales and wait until the scales are stable.
- 2. Press [▶] and then use [▶] or [♦] to set the persons height. Then press again on [▶] to exit and view the calculated BMI.
- 3. The BMI value disappears when the person leaves the scale but can be recalled with 🛞

Replacing batteries:

1. Disconnect the power supply to the scale.

2. Remove the battery cover on the back of the indicator. Insert 6 pcs. new AA batteries and make sure the poles are seated correctly.

4. Close the battery cover.





NOTE! Do **not** use rechargeable batteries. If you do, the batteries should be charged in an external charger. The scale adapter cannot charge the batteries when they are in the scale.

Cleaning.

Cleaning / Disinfection

During all maintenance work with the chair scale, the power supply must be cut off.

The chair with seat and backrest may only be cleaned with household cleaners or disinfectants, e.g. 70% isopropanol solution.

We recommend a disinfectant that is intended for disinfection by wet drying the surfaces of the chair scale.

There, follow the manufacturer's instructions.

Do not use polishes or aggressive cleaners such as alcohol, gasoline or anything else, as they can damage the surfaces that are made of plastic or rubber.

Assembling:

1. Take out the load cell signal cable.



2. Load cell signal cable go through the column.

2019-09-25



3. Screw the column tightly as below.

4. Load cell signal cable go through the indicator holder.

5. Connect indicator cable and fasten the fixed knob.

2019-09-25

