

## Indicator RWS

RWS – Stainless steel indicator IP class according to IP-65. OIML Type approved. 22 mm LCD display with backlight and rechargeable battery included.



- ✓ Compact design in stainless steel according to IP-65.
- ✓ OIML type approved 6.000d or 2x3.000d.
- ✓ Easy to use.
- ✓ LCD display – with 22mm digits and backlight.
- ✓ 4 x 350ohm loadcell can be connected.
- ✓ RS-232C function as standard.
- ✓ Rechargeable battery included.
- ✓ Automatic or manual weight accumulation.
- ✓ Multi-Range
- ✓ 100% Tare range.

## RWS Indicator Specifications:

### Analog Specification:

Loadcell excitation:	5V DC.
Max. loadcell input:	15 mV.
Display resolution:	Max: 150.000.
A/D converging rate:	Max. 60 times / sec.
Internal resolution:	600.000 internal resolutions.
Number of loadcells:	Max. 4 loadcells (350 ohm).

### Digital Specification:

Display type:	LCD display with backlight. 6 digits, height 22 mm.
Display resolution:	1, 2, 5, 10, 20, 50
Decimal point:	0 to 0.0000
Key functions:	Unit, Print/M+, Gross Net, Tare, Zero, On/Off

### Standard I/F:

Communication RS-232	Manual via print, stream mode and command mode
----------------------	--

### Power Requirement:

Adapter specification:	Input: 100/230V AC 50/60Hz Output: 12V / 500mA
Standard battery:	7,2V HI-MH / 2000mAh, rechargeable battery kit
Power consumption:	4 loadcells + backlight. = 10 hours 1 loadcell + no backlight = 50 hours

### General:

Operating temperature:	-10°C till 40°C
Operating humidity:	< 85% RH Max. (none condensing)
Net weight:	950g (including table /wall bracket.).
Size:	L 196 x H 119 x D 65 mm